

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A front body structure of a vehicle, comprising:

a pair of right and left front side ~~members (10, 12)~~members disposed at a front portion of a vehicle body along a longitudinal direction of the vehicle body;

a connecting ~~member (20)~~member including ~~ends (22A, 24A, 22B, 24B)~~a pair of front end and a pair of rear ends in a transverse direction of the vehicle, the ~~ends (22A, 24A) and the ends (22B, 24B)~~the front ends being respectively fixed to front fixing ~~portions (10B, 12B)~~portions and the rear ends being respectively fixed to rear fixing portions (10C, 12C) portions of the pair of right and left front side ~~members (10, 12);~~members; and

fixing ~~mechanisms (50, 52)~~mechanisms disposed on the right and left rear fixing ~~portions (10C, 12C);~~portions, the fixing ~~mechanisms (50, 52)~~mechanisms releasing, when a load applied to the front side ~~members (10, 12)~~members from a front side of the vehicle is equal to or more than a predetermined value at a time of full-lapped collision, a state in which the front side ~~members (10, 12)~~members are fixed to the connecting ~~member (20);~~member, and maintaining, at a time of offset collision, a state in which the collided front side ~~member (10 or 12)~~member is fixed to the connecting ~~member (20);~~member,

wherein the fixing mechanisms include slits extending parallel to the front side members and first branches branching from vicinities of rear-end openings of the slits toward inner rear sides of the vehicle, and fixing members of the connecting member can move in the slits and the first branches, and

the first branches are structured such that, at the time of offset collision, the fixing members fixing the connecting member to the collided front side member move and fit into the first branch of the slit.

2. (Currently Amended) The front body structure of a vehicle of claim 1, wherein the connecting ~~member (20)~~member is a front suspension ~~member (20)~~member.

3. (Currently Amended) A front body structure of a vehicle, comprising:  
a pair of right and left front side members disposed at a front portion of a  
vehicle body along a longitudinal direction of the vehicle body;  
a connecting member including a pair of front ends and a pair of rear ends in a  
transverse direction of the vehicle, the front ends being respectively fixed to front fixing  
portions and the rear ends being respectively fixed to rear fixing portions of the pair of right  
and left front side members; and  
fixing mechanisms disposed on the right and left rear fixing portions, the  
fixing mechanisms releasing, when a load applied to the front side members from a front side  
of the vehicle is equal to or more than a predetermined value at a time of full-lapped collision,  
a state in which the front side members are fixed to the connecting member, and maintaining,  
at a time of offset collision, a state in which the collided front side member is fixed to the  
connecting member, wherein~~The front body structure of a vehicle of claim 1, wherein~~

the fixing mechanisms (50, 52)mechanisms include slits (82)slits extending  
parallel to the front side members (10, 12)members and first branches (82B)branches  
branching from vicinities of rear-end openings (82A)openings of the slits (82)slits toward  
inner rear sides of the vehicle, and fixing members (58, 60, 72)members of the connecting  
member (20)member can move in the slits (82)slits and the first branches (82B)branches.

4. (Canceled)

5. (Currently Amended) The front body structure of a vehicle of ~~claim 3,~~claim 1, wherein the ~~slits (82)~~slits further include second ~~branches (82D)~~branches branching toward outer rear sides of the vehicle.

6. (Currently Amended) The front body structure of a vehicle of ~~claim 3,~~claim 1, wherein the second ~~branches (82B)~~branches are structured such that, at the time of offset collision, the fixing ~~members (58 or 60, and 72)~~members fixing the connecting ~~member (20)~~member to the other front side ~~member (10 or 12)~~member opposite to the collided front side ~~member (10 or 12)~~member move and fit into the second ~~branch (82B)~~branch of the slit ~~(82)~~slit.

7. (Currently Amended) A front body structure of a vehicle, comprising:  
a pair of right and left front side members disposed at a front portion of a  
vehicle body along a longitudinal direction of the vehicle body;  
a connecting member including a pair of front ends and a pair of rear ends in a  
transverse direction of the vehicle, the front ends being respectively fixed to front fixing  
portions and the rear ends being respectively fixed to rear fixing portions of the pair of right  
and left front side members; and  
fixing mechanisms disposed on the right and left rear fixing portions, the  
fixing mechanisms releasing, when a load applied to the front side members from a front side  
of the vehicle is equal to or more than a predetermined value at a time of full-lapped collision,  
a state in which the front side members are fixed to the connecting member, and maintaining,  
at a time of offset collision, a state in which the collided front side member is fixed to the  
connecting member, wherein~~The front body structure of a vehicle of claim 1, wherein~~  
the fixing ~~mechanisms (50, 52)~~mechanisms include slits ~~(82)~~slits which extend parallel to the front side ~~members (10, 12)~~members and in which fixing ~~members (58, 60, 72)~~members of the connecting ~~member (20)~~member can move, and movement restraint ~~mechanisms (82C)~~mechanisms for restraining movement of the connecting ~~member (20)~~member are formed in inner peripheral surfaces of the ~~slits (82)~~slits.

8. (Currently Amended) A front body structure of a vehicle, comprising:

a pair of right and left front side members disposed at a front portion of a vehicle body along a longitudinal direction of the vehicle body;

a connecting member including a pair of front ends and a pair of rear ends in a transverse direction of the vehicle, the front ends being respectively fixed to front fixing portions and the rear ends being respectively fixed to rear fixing portions of the pair of right and left front side members; and

fixing mechanisms disposed on the right and left rear fixing portions, the fixing mechanisms releasing, when a load applied to the front side members from a front side of the vehicle is equal to or more than a predetermined value at a time of full-lapped collision, a state in which the front side members are fixed to the connecting member, and maintaining, at a time of offset collision, a state in which the collided front side member is fixed to the connecting member, wherein  
~~The front body structure of a vehicle of claim 1, wherein~~

the fixing mechanisms (50, 52) ~~mechanisms~~ include slits (82) ~~slits~~ which extend parallel to the front side members (10, 12) ~~members~~ and in which fixing members (58, 60, 72) ~~members~~ of the connecting member (20) ~~member~~ can move, and lock mechanisms (92) ~~mechanisms~~ for opening and closing opening ends (82A) ~~ends~~ are provided near the slits (82) ~~slits~~, and at the time of offset collision, the lock mechanism (92) ~~mechanism~~ closes the opening end (82A) ~~end~~ of the slit (82) ~~slit~~ of the fixing mechanism (50 or 52) ~~mechanism~~ provided on the collided front side member (10 or 12) ~~member~~, based on detection signals from collision detection sensors (86, 88) ~~sensors~~ disposed at a front portion (84A) ~~portion~~ of the vehicle body (84) ~~body~~.

9. (Currently Amended) The front body structure of a vehicle of claim 1, structured such that reaction force (F1) ~~force~~ of the right and left front side members (10, 12) ~~members~~ at the time of full-lapped collision becomes substantially equal to total reaction force (F5) ~~force~~ at the time of offset collision.

10. (Currently Amended) The front body structure of a vehicle of claim 9, structured such that, at the time of offset collision, the connecting ~~member (20)~~member receives a part of the collision load the collided front side ~~member (10 or 12)~~member receives so that a part of impact can be absorbed.